



## Type of luminaire

Type of luminaire	Wall light,
Photometric body	Light discovered
Characteristics of the luminaire	A luminaire with a modern design, combining a decorative crystal lampshade with a durable and stable luminaire base

## General information

Materials	Powder painted aluminum cast. Lens - crystal glass, satin inside. The lampshade may take on an amber color over time. Nylon6 cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø5mm, spacing 34x54mm
Terminal	Connection terminals: max 2x2,5mm <sup>2</sup> . Possibility to connect the luminaire in loops max 2x1,5mm <sup>2</sup> . Round insulated cable with a diameter of max ø12,5mm
Type of light source	LED module AC integrated Replaceable (LED only) light source by an end-user.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Box dimensions [cm]	24cm x 15,5cm x 11,5cm

## Technical data

LED module	Yes
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	4W
Luminaire wattage	4W
Lamp luminous flux	439lm
Luminaire luminous flux	330lm
Efficiency of the luminaire	82,5lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
THD factor	< 20%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
Inrush current	17mA / 60ms

## Spare parts

ZS1251zx0009	Service set.
--------------	--------------

## Files to download

Manual
--------

## Indexes

Index	Color	RAL
1251BL	BLACK	9005
1251GR	GRAPHITE	7016

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.