



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Top-shaded rotationally symmetrical light.
Characteristics of the luminaire	Column luminaire with a stable and durable construction. Designed for lighting private areas and public zones.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Mounting of the fixture: 3 holes \varnothing 9mm on a \varnothing 65mm diameter, 120° apart.
Terminal	Connection terminals: max 3x2.5mm ² , possibility of connecting the luminaire in a loop max 3x2.5mm ² . Cable in a round sheath with a maximum diameter of \varnothing 12.5mm.
Type of light source	LED E27 lamp Replaceable (LED only) light source by an end-user.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)

Technical data

LED Lamp E27	Yes
External control	Phase dimming LED GU10 E27 (User manual)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	806lm
Luminaire luminous flux	100lm
Efficiency of the luminaire	12,5lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Power Factor luminaire	PF 0,70
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class / EPREL

Accessories sold separately

3086GA0009	Mounting adapter
205ZX0010	Concreting anchor
206GA0S10	Adapter for concrete foundation
206GA0010	Ground anchor
3080GA0009	Mounting adapter

Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

Spare parts

06291001	Lampshade - service kit
08288004	Gasket.
46999021	LEDE27 lamp

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1475.01BL	BLACK	9005
1475.01GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.