



### Type of luminaire

|                                  |   |
|----------------------------------|---|
| Type of luminaire                | Post light fixture.   |
| Photometric body                 | Rotationally symmetric light shaded from above.   |
| Characteristics of the luminaire | Bollard luminaire of stable and durable construction. For lighting private areas and public spaces. |

### General information

|                              |   |
|------------------------------|---|
| Materials                    | Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.  |
| Mounting method              | Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every $120^\circ$ .  |
| Terminal                     | Connection terminals: max $3 \times 4\text{mm}^2$ , possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$ . A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$ . |
| Type of light source         | LED module AC integrated<br>Replaceable (LED only) light source by a professional.  |
| Light control                | Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)  |
| Luminaire weight net / gross | 6,6kg / 6,6kg   |
| Box dimensions [cm]          | 21cm x 21,5cm x 5,7cm   |

### Technical data

|                                     |                          |
|-------------------------------------|--------------------------|
| LED module                          | Yes                      |
| Light source wattage                | 10W                      |
| Luminaire wattage                   | 10W                      |
| Lamp luminous flux                  | 900lm                    |
| Luminaire luminous flux             | 136lm                    |
| Efficiency of the luminaire         | 13,6lm/W                 |
| Color temperature                   | 3000K                    |
| Colour consistency (McAdam ellipse) | SDCM3                    |
| Colour rendering index CRI          | 80                       |
| L70B50 [wg LM-80]                   | >50 000h                 |
| Power Factor luminaire              | PF > 0,99                |
| Ta Rated temperature                | +25°C                    |
| Ambient operating temp. range       | Ta max=+65°C             |
| Inrush current                      | 46,1mA/500 $\mu\text{s}$ |
| BUG rating                          | B0-U2-G1                 |

### Accessories sold separately

|            |                                 |
|------------|---------------------------------|
| 3086GA0009 | Mounting adapter                |
| 3080GA0009 | Mounting adapter                |
| 206GA0010  | Ground anchor                   |
| 206GA0S10  | Adapter for concrete foundation |
| 205ZX0010  | Concreting anchor               |

### Spare parts

|              |                         |
|--------------|-------------------------|
| 06291001     | Lampshade - service kit |
| 08288004     | Gasket.                 |
| 46999366     | LED module.             |
| ZS1476zx0011 | Service set.            |

### Files to download

|                       |                       |
|-----------------------|-----------------------|
| Photometric LDT files | Photometric IES files |
| Manual                |                       |

### Indexes

| Index  | Color               | RAL  |
|--------|---------------------|------|
| 1476BL | BLACK               | 9005 |
| 1476GA | HOT-DIP GALVANIZING | -    |

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.