



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Top-shaded rotationally symmetrical light.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

General information

Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire : 3 holes ø9mm in diameter ø65mm every 120 °. Other accessories must be purchased separately
Terminal	Connection terminals: max 3x2.5mm ² , possibility to connect the luminaire in loops, max 3x1.5mm ² . Round insulated cable with a diameter of max ø12.5mm
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Box dimensions [cm]	21cm x 21,5cm x 57cm

Technical data

LED module	Yes
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1098lm
Luminaire luminous flux	159lm
Efficiency of the luminaire	15,9lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF 0,99
THD factor	20%
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class / EPREL

Inrush current	43mA / 60ms
BUG rating	B0-U2-G1

Accessories sold separately

3086GA0009	Mounting adapter
205ZX0010	Concreting anchor
206GA0S10	Adapter for concrete foundation
206GA0010	Ground anchor
3080GA0009	Mounting adapter

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1476BL	BLACK	9005
1476GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.