



### Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Top-shaded rotationally symmetrical light.
Characteristics of the luminaire	A pillar fixture with a stable and durable construction. For lighting private areas and public spaces.

### General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9$ mm with a diameter of $\varnothing 65$ mm every $120^\circ$ .
Terminal	Connection terminals: max $3 \times 4$ mm <sup>2</sup> , possibility to connect luminaire in loop max $3 \times 2,5$ mm <sup>2</sup> . A round wire in the isolation with a diameter of max $\varnothing 12,5$ mm.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	9,8kg / 9,8kg
Box dimensions [cm]	21cm x 21cm x 57cm

### Technical data

LED module	Yes
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	900lm
Luminaire luminous flux	136lm
Efficiency of the luminaire	13,6lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Power Factor luminaire	PF > 0,99
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
Inrush current	46,1mA/500 $\mu$ s
BUG rating	B0-U2-G1

### Accessories sold separately

3086GA0009	Mounting adapter
205ZX0010	Concreting anchor
206GA0S10	Adapter for concrete foundation
206GA0010	Ground anchor
3080GA0009	Mounting adapter

### Spare parts

06291001	Lampshade - service kit
08288004	Gasket.
46999366	LED module.

### Files to download

Photometric LDT files	Photometric IES files
Manual	

### Indexes

Index	Color	RAL
1479BL	BLACK	9005
1479GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.