



### Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Rotationally symmetric light shaded from above.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

### General information

Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ in diameter $\varnothing 65\text{mm}$ every $120^\circ$ . Other accessories must be purchased separately
Terminal	Connection terminals: max $3 \times 2.5\text{mm}^2$ , possibility to connect the luminaire in loops, max $3 \times 1.5\text{mm}^2$ . Round insulated cable with a diameter of max $\varnothing 12.5\text{mm}$
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	9,3kg / 10,7kg
Box dimensions [cm]	20,5cm x 20,5cm x 91cm

### Technical data

LED module	Yes
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1098lm
Luminaire luminous flux	159lm
Efficiency of the luminaire	15,9lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70B50 [wg LM-80]	50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Ambient operating temp. range	Ta max=+65°C

This product contains light source of energy efficiency class **A** / **E**PREL

Inrush current	43mA / 60ms
BUG rating	B0-U2-G1

### Accessories sold separately

3086GA0009	Mounting adapter
3080GA0009	Mounting adapter
206GA0010	Ground anchor
206GA0S10	Adapter for concrete foundation
205ZX0010	Concreting anchor

### Spare parts

06291001	Lampshade - service kit
08288004	Gasket.
ZS1479zx0012	Service set.

### Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD



**Indexes**

Index	Color	RAL
1479BL	BLACK	9005
1479GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.