



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Light discovered
Characteristics of the luminaire	A luminaire with a modern design, which uses a combination of a decorative crystal lampshade with a durable and stable luminaire casing

General information

Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. The lampshade may take on an amber color over time.
Mounting method	Mounting of the luminaire: 2 holes \varnothing 6,8mm, spacing 38mm, Other accessories must be purchased separately
Terminal	Connection terminals: max 3x2,5mm ² , Possibility to connect luminaire in loop max 3x2,5mm ² , Round insulated cable with a diameter of max \varnothing 12,5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	5,8kg / 6,9kg

Technical data

LED module	Yes
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	4W
Luminaire wattage	4W
Lamp luminous flux	352lm
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L70B50 [wg LM-80]	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF 0,95
THD factor	20%
Ta Rated temperature	+25°C
Ambient operating temp. range	Ta max=+65°C
Inrush current	17mA / 60ms

Accessories sold separately

204GA0009	Ground anchor
203ZX0009	Concreting anchor

Spare parts

ZS1561zx0008	Service set.
--------------	--------------

Files to download

Manual

Indexes

Index	Color	RAL
1561BL	BLACK	9005
1561GR	GRAPHITE	7016
1561GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.