



Type of luminaire

| | |
|----------------------------------|---|
| Type of luminaire | Post light fixture. |
| Photometric body | Light discovered |
| Characteristics of the luminaire | A luminaire with a modern design, which combines a decorative crystal lampshade with a durable and stable base. |

General information

| | |
|----------------------|--|
| Materials | Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. The lampshade may take on an amber color over time. |
| Mounting method | Mounting of the luminaire: 2 holes \varnothing 6.8mm at a distance of 38mm |
| Terminal | Connection terminals: max 2x2.5mm ² Possibility of connecting the luminaire in loops of max. 2x2.5mm ² Round insulated cable with a maximum diameter of \varnothing 12.5mm |
| Type of light source | LED module AC integrated Replaceable (LED only) light source by a professional. |
| Light control | Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE) |
| Box dimensions [cm] | 89,5cm x 11,5cm x 11,5cm |

Technical data

| | |
|-------------------------------------|--|
| LED module | Yes |
| External control | Phase dimmer Lumens LED AC (User manual) |
| Light source wattage | 4W |
| Luminaire wattage | 4W |
| Lamp luminous flux | 466lm |
| Luminaire luminous flux | 345lm |
| Efficiency of the luminaire | 86,3lm/W |
| Color temperature | 4000K |
| Colour consistency (McAdam ellipse) | SDCM3 |
| Colour rendering index CRI | 80 |
| LED photobiological threat | RG0 or RG1 |
| Power Factor luminaire | PF>0,98 |
| Ta Rated temperature | +25°C |
| Ambient operating temp. range | TA MAX=+65°C |

This product contains light source of energy efficiency class **E** / **EPREL**

| | |
|----------------|-------------|
| Inrush current | 17mA / 60ms |
| BUG rating | B0-U3-G0 |

Accessories sold separately

| | |
|-----------|-------------------|
| 204GA0009 | Ground anchor |
| 203ZX0009 | Concreting anchor |

Spare parts

| | |
|--------------|--------------|
| ZS1562zx0010 | Service set. |
|--------------|--------------|

Files to download

| | |
|-----------------------|-----------------------|
| Photometric LDT files | Photometric IES files |
| Manual | |

Indexes

| Index | Color | RAL |
|--------|---------------------|------|
| 1562BL | BLACK | 9005 |
| 1562GR | GRAPHITE | 7016 |
| 1562GA | HOT-DIP GALVANIZING | - |

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.