



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Light discovered
Characteristics of the luminaire	A luminaire with a modern design, combining a decorative crystal lampshade with a durable and stable luminaire base

General information

Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. The lampshade may take on an amber color over time.
Mounting method	Mounting of the luminaire: 2 holes \varnothing 6,8mm, spacing 38mm.
Terminal	Connection terminals: max 2x2,5mm ² , Possibility to connect luminaire in loop max 2x2,5mm ² . Round insulated cable with a diameter of max \varnothing 12,5mm.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)

Technical data

LED module	Yes
External control	Phase dimmer Lumens LED AC (User manual)
Light source wattage	4W
Luminaire wattage	4W
Lamp luminous flux	466lm
Luminaire luminous flux	345lm
Efficiency of the luminaire	86,3lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,98
Ta Rated temperature	+25°C
Ambient operating temp. range	TA MAX=+65°C

This product contains light source of energy efficiency class **A** / **EPREL**

Inrush current	17mA / 60ms
BUG rating	B0-U3-G0

Accessories sold separately

204GA0009	Ground anchor
203ZX0009	Concreting anchor

Spare parts

ZS1567zx0009	Service set.
--------------	--------------

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1567BL	BLACK	9005
1567GR	GRAPHITE	7016
1567GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.