



### Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Top-shaded rotationally symmetrical light.
Characteristics of the luminaire	Pole light fixture with a stable and durable construction. For illuminating private areas and other architectural concepts.

### General information

Materials	Wood - scandinavian painted pine and hot-dip galvanized steel. Wood - scandinavian painted pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixture mounting: 3 holes $\varnothing 9\text{mm}$ on a diameter of $\varnothing 65\text{mm}$ every $120^\circ$ . As per the attached installation instructions. Other accessories need to be purchased separately.
Terminal	Connection terminals: max $2 \times 4\text{mm}^2$ , possibility to connect the fitting in a loop max $2 \times 4\text{mm}^2$ . Cable in a round cover with a maximum diameter of $\varnothing 12.5\text{mm}$ .
Type of light source	LED module, electronic power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Phase-dimming (TRIAC) TRAILING EDGE (TE) - LEADING EDGE (LE)
Luminaire weight net / gross	6,08kg / 7,44kg
Box dimensions [cm]	20,5cm x 20,5cm x 91cm

### Technical data

LED module	Yes
Driver	Yes
Driver durability	50000h
External control	Dim. TRIAC (KGP) (User manual)
Light source wattage	6,7W
Luminaire wattage	8,5W
Lamp luminous flux	1059lm
Luminaire luminous flux	146lm
Efficiency of the luminaire	17,2lm/W
ULOR	10%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
L80B20 [wg LM-80]	>50 000h
L90B10 [wg LM-80]	>38 000h
Power Factor luminaire	PF 0,90
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C

This product contains light source of energy efficiency class **A** / **D** / EPREL

Optionally, the fixture is also available:

- in a safety version for Class I
- for LED color 2700K [I/I]
- for a different luminous flux value
- in a version with a surge protection device (SPD)
- for a different fixture color (according to the RAL color palette)
- for a different fixture height

Sales conditions and other information, in agreement with the Norlys Commercial Department.

BUG rating	B0-U2-G1
------------	----------

### Accessories sold separately

3086GA0009	Mounting adapter
205ZX0010	Concreting anchor
206GA0S10	Adapter for concrete foundation
206GA0010	Ground anchor
3080GA0009	Mounting adapter

### Spare parts

ZS1665zx0009	Service set.
--------------	--------------



## Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual
BIM ArchiCAD	

## Indexes

Index	Color	RAL
1665BL	BLACK	9005
1665GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.