



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Top-shaded rotationally symmetrical light.
Characteristics of the luminaire	A post-mounted luminaire with a stable and durable construction. For lighting private areas and public zones.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Luminaire mounting: 3 holes $\varnothing 9\text{mm}$ on $\varnothing 65\text{mm}$ diameter every 120° .
Terminal	Connection terminals: max $3 \times 4\text{mm}^2$, possibility of connecting the fixture in a loop max $3 \times 2.5\text{mm}^2$. Round cable with a maximum diameter of $\varnothing 12.5\text{mm}$.
Type of light source	Lamp E27
Luminaire weight net / gross	8,83kg / 10,26kg
Box dimensions [cm]	20,5cm x 20,5cm x 91cm
Luminaire dimensions [cm]	12cm x 12cm x 49cm

Technical data

Lamp E27	Yes
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C
Ambient operating temp. range	-20...+45°C
Possibility to order luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).	
BUG rating	B0-U1-G0

Accessories sold separately

3086GA0009	Mounting adapter
205ZX0010	Concreting anchor
206GA0S10	Adapter for concrete foundation
206GA0010	Ground anchor
3080GA0009	Mounting adapter

Recommended light sources

Osram ECO PRO Classic 46 => 60W E27	Philips ECO Classic 42 => 60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Spare parts

06291001	Lampshade - service kit
08288004	Gasket.
46999021	LEDE27 lamp

Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual

Indexes

Index	Color	RAL
291BL	BLACK	9005
291GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.