



Type of luminaire

Type of luminaire	Post light fixture.
Photometric body	Rotationally symmetric light shaded from above.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every 120° .
Terminal	Connection terminals: max $3 \times 4\text{mm}^2$, possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$. A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$.
Type of light source	Lamp E27 Replaceable light source by an end-user.
Luminaire weight net / gross	5,28kg / 6,31kg
Box dimensions [cm]	21cm x 21,5cm x 57cm
Luminaire dimensions [cm]	15cm x 15cm x 49cm

Technical data

Lamp E27	Yes
Light source wattage	LED max 9W
Luminaire wattage	LED max 9W
ULOR	11%
Ta Rated temperature	+25°C
Ambient operating temp. range	TA MAX=+65°C
Possibility to order luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).	
BUG rating	BO-U1-GO

Accessories sold separately

3086GA0009	Mounting adapter
3080GA0009	Mounting adapter
206GA0010	Ground anchor
206GA0S10	Adapter for concrete foundation
205ZX0010	Concreting anchor

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46 \leftrightarrow 60W E27	Philips ECO Classic 42 \leftrightarrow 60W E27

Spare parts

06291001	Lampshade - service kit
08288004	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
293BL	BLACK	9005
293GA	HOT-DIP GALVANIZING	-

Other colors according to the "Colors Template" pattern book - available on request, subject to agreement with Norlys' Sales Department.